

Atrie
CE

WireSpan 5000B

xDSL Bridge

We Bring a World of Experience to Data Communication



Key Feature

Line interface:	Rate-selectable single-pair high speed Digital Subscriber Line capable of Full duplex symmetric operation up to 2.320 Mbps
Line Coding:	2B1Q
Line Rate:	256Kbps, 384Kbps, 768Kbps, 1.024Mbps, 1.280Mbps, 1.536Mbps, 2.048Mbps, 2.320Mbps
Transmit Level:	13.5 \pm 0.5dBm
Connector:	RJ-11
LAN Interface:	Auto-sensing 10/100 BASE-T Ethernet
Connector:	TWO RJ-45 (to PC or HUB)
Range:	3.2Km for 24AWG, at 2.320Mbps 6.2Km for 24AWG, at 256Kbps
Bridging:	Dynamically learning and aging up to 1,024 MAC addresses Filtering Rates 14,800pps (10Mbps)
Management Configuration:	Use DIP Switch
Status:	Use Console port (DB9)
LED Indicator:	PWR, TST, LINK, ACT, SYN, SQ
Physical Dimensions:	161mm(W) x 127.5mm(D) x 37mm(H)
Power Requirement:	
Input Voltage:	12VAC \pm 10%, 0.8A
Power Consumption :	4W (MAX)
Environment:	
Operating Temperature:	0 ϕ J to 50 ϕ J
Relative Humidity:	0% to 95% non-condensing



ATRIE

TECHNOLOGY INC.

10F, 14, Lane 609, Sec. 5, Chung Hsin Rd.,
San Chung City, Taipei Hsien, Taiwan, 241, R.O.C.
TEL:+886-2-29995155 FAX:+886-2-29994960

<http://www.atrie.com.tw> contacts@mail.atrie.com.tw <http://www.atrie.com.tw> contacts@mail.atrie.com.tw